

HOW TO READ THE MAXIMUM VALUES TABLE

The feature or functional area of clustered Data ONTAP related to the maximum value

The level of scope in which the maximum value applies within the cluster

Applies to HA pair and cluster scope and indicates "yes" if the node maximum value doubles in failover (HA pair scope) or if the node limits scales by the maximum number of nodes in the cluster

Indicates which clustered Data ONTAP versions support the platform and maximum values indicated for the column

Platform maximum values listed by platform model

Clustered Data ONTAP 8.2, 8.2.1 Maximum Configurations Guide

Small-Sized Clusters (4 nodes)

Category	Description	Scope	Code Enforced	Scales by Scope	7-Mode	Platform Agnostic	Cluster Maximum	Platform Maximum														
Core	Maximum number of nodes - NAS	N/A	N/A	N/A	N/A	N/A	4	<table border="1"> <thead> <tr> <th>Platform Model</th> <th>Platform Maximum</th> </tr> </thead> <tbody> <tr> <td>FA52220</td> <td>8.2, 8.2.1</td> </tr> <tr> <td>FA52240</td> <td>8.2, 8.2.1</td> </tr> <tr> <td>FA53160</td> <td>8.2, 8.2.1</td> </tr> <tr> <td>FA53170</td> <td>8.2, 8.2.1</td> </tr> <tr> <td>FA53210</td> <td>8.2, 8.2.1</td> </tr> <tr> <td>FA53240</td> <td>8.2, 8.2.1</td> </tr> </tbody> </table>	Platform Model	Platform Maximum	FA52220	8.2, 8.2.1	FA52240	8.2, 8.2.1	FA53160	8.2, 8.2.1	FA53170	8.2, 8.2.1	FA53210	8.2, 8.2.1	FA53240	8.2, 8.2.1
		Platform Model	Platform Maximum																			
FA52220	8.2, 8.2.1																					
FA52240	8.2, 8.2.1																					
FA53160	8.2, 8.2.1																					
FA53170	8.2, 8.2.1																					
FA53210	8.2, 8.2.1																					
FA53240	8.2, 8.2.1																					
N/A	N/A	N/A	N/A	N/A	N/A																	

Supported Data ONTAP Versions >>>

A generic description of the maximum value that, combined with each level of "scope," provides a complete context to the maximum value

Indicates if the maximum value is code enforced by clustered Data ONTAP

Indicates whether an equivalent or related maximum value is present in 7-Mode that should be considered when planning a transition to clustered Data ONTAP

The cluster maximum value for the indicated size of the cluster for this document (small - 4 nodes, medium - 8 nodes, or large - 24 nodes) that applies to both homogenous and heterogeneous clusters

Platform-specific maximum values as they relate to the scope column

HOW SCOPE APPLIES TO CLUSTER AND PLATFORM MAXIMUM VALUES

Category	Description	Scope	Code Enforced	Scales by Scope	7-Mode	Platform Agnostic	Cluster Maximum	Platform Maximum
		Node	N/A	N/A	N/A	N/A	25	FA56000
		Node	Yes	N/A	Yes	Yes		9.2, 9.2.1
		HA Pair	Yes	N/A	Yes	Yes		100
		Cluster	Yes	Yes	Yes	Yes		200
		Node	N/A	N/A	N/A	N/A		25
WAFL	Maximum number of FlexCache® volumes	Node	N/A	N/A	N/A	N/A	25	FA56000
		Node	Yes	N/A	Yes	Yes		9.2, 9.2.1
		HA Pair	Yes	N/A	Yes	Yes		100
		Cluster	Yes	Yes	Yes	Yes		200
		Node	N/A	N/A	N/A	N/A		25
WAFL	Maximum number of concurrent DataMotion™ for Volumes (vol move) operations	Node	No	N/A	Yes	Yes	25	FA56000
		Node	No	N/A	Yes	Yes		9.2, 9.2.1
		HA Pair	No	N/A	Yes	Yes		100
		Cluster	No	No	Yes	Yes		200
		Node	No	N/A	No	Yes		25

The HA pair, node, and any subnode row of scope, along with the code enforced, scales by scope, 7-Mode, and platform-agnostic columns in the same row, apply to the various platform maximum value column entries located to the right of the cluster column

The cluster row of scope, along with the code enforced, scales by scope, 7-Mode, and platform-agnostic columns in the same row, only apply to the cluster maximum column

"N/A" in the cluster maximum column indicates that the maximum value is not a cluster resource, whereas any number that is specified in this field indicates that the maximums/objects are tracked as a cluster resource

UNDERSTANDING SCALES BY SCOPE FOR AN HA PAIR

YES: If the HA pair row Scales by Scope column is "yes," the platform maximum value entry for the HA pair row is double that of the node row, indicating that the node maximum value is doubled in failover

Category	Description	Scope	Code Enforced	Scales by Scope	7-Mode	Platform Agnostic	Cluster Maximum	Platform Maximum
WAFL	Maximum number of FlexCache® volumes	N/A	N/A	N/A	N/A	N/A	25	FA56080 8.2, 8.2.1 Platform Maximum 100 200
		Node	Yes	N/A	Yes	Yes	500	
		HA Pair	Yes	Yes	No	Yes	200	
		Cluster	Yes	Yes	No	Yes	200	
WAFL	Maximum number of concurrent DataMotion™ for Volumes (vol move) operations	N/A	N/A	N/A	N/A	N/A	25	FA56080 8.2, 8.2.1 Platform Maximum 100 200
		Node	Yes	N/A	Yes	Yes	500	
		HA Pair	No	No	Yes	Yes	25	
		Cluster	No	No	Yes	Yes	25	

NO: If the HA pair row Scales by Scope column is "no," the platform maximum value entry for the HA pair row is the same as that of the node row, indicating that the node maximum value is not doubled in failover

UNDERSTANDING SCALES BY SCOPE FOR A CLUSTER

Category	Description	Scope	Code Enforced	Scales by Scope	7-Mode	Platform Agnostic	Cluster Maximum	Platform Maximum
								FA 56080
								Platform Maximum
WAFL	Maximum number of FlexCache® volumes	N/A	N/A	N/A	N/A	N/A	2,400	8.2, 8.2.1 N/A 100 200
WAFL	Maximum number of concurrent DataMotion™ for Volumes (vol move) operations	N/A	N/A	N/A	N/A	N/A	25	N/A 25 25 25

YES: If the cluster row Scales by Scope column is "yes," the cluster maximum value entry scales in relation to the maximum number of nodes supported for the cluster

NO: If the cluster row Scales by Scope column is "no," the cluster maximum value entry does not scale based on the maximum number of nodes supported for the cluster

NOTES AND CAVEATS

Maximum values in this document represent the maximum value supported by NetApp in any configuration.

Consult additional technical documentation (technical reports and more) for operational guidance, best practices, and recommendations for specific application or performance-sensitive environments.

The primary resource affected by maximum values is system memory. As a result, all sizing and design considerations around maximum values must consider overall impact to available system memory.

Special attention must be paid to maximum values that are not code enforced, because in many cases there is no warning that a maximum value will be or has been exceeded.

Special consideration must be given to maximum values that have related or equivalent maximum values in 7-Mode, because the context of how the maximum values apply may have changed, or the maximum values may be lower (or higher) than it was in 7-Mode. For example, 7-Mode uses qtree policies, whereas clustered Data ONTAP uses both qtree policies and rules; although they are named the same in both ONTAP versions, the specific implementation is different.

For node maximum values that do not scale across HA failover (HA pair and node maximum values are the same), NetApp recommends operating at half of the defined maximum value (not required) on a per-node basis to make sure that maximum values are not exceeded in failover. It is possible to operate at any distribution between the two nodes in the HA pair, so long as in failover the remaining node does not exceed the defined maximum value.

Clustered Data ONTAP platform mixing rules (link below) take precedence in all cases. Each sized cluster now includes "primary platforms" and "mixable platforms" entries that define which platforms are able to be mixed together based on the defined platform mixing rules. When mixing platforms across different-sized clusters, the cluster maximum values for the specific size of cluster apply, while the individual subnode, node, and HA pair maximum values continue to apply based on the platform model being used.

[Clustered Data ONTAP Platform Mixing Rules](https://fieldportal.netapp.com/Core/DownloadDoc.aspx?documentId=931268&contentId=125939)

<https://fieldportal.netapp.com/Core/DownloadDoc.aspx?documentId=931268&contentId=125939>

The maximum values listed in this document are valid only through the expiration date that is listed to the right of the main title bar. After expiration, visit the NetApp Field Portal to obtain the latest version of the maximum configurations document.

Future releases of this document will expand clustered Data ONTAP maximum values information into additional feature and functional areas. Additionally, existing maximum values will be revised and expanded.



Clustered Data ONTAP 8.3.x Maximum Configurations: Release 3.0

Author: Jay White | Published: June 26, 2015

Copyright © 2014 NetApp, Inc. All rights reserved. No portions of this document may be reproduced without prior written consent of NetApp, Inc. Specifications are subject to change without notice. NetApp, the NetApp logo, Go further, faster, DataMotion, Data ONTAP, FlexCache, Snapshot, and WAFL are trademarks or registered trademarks of NetApp, Inc. in the United States and/or other countries. All other brands or products are trademarks or registered trademarks of their respective holders and should be treated as such.

This document is for informational purposes only. Actual performance depends on the product configuration as determined by the end user or the end user's appointed service provider. NetApp assumes no responsibility for errors or omissions in this document. All information in this document is based on NetApp's current knowledge and understanding of the products evaluated by NetApp (or third parties operating on behalf of NetApp) and the methodology and assumptions used by NetApp. Such information in no way constitutes any legally binding warranty, representation, or other legal commitment or obligation for NetApp.

THIS DOCUMENTATION AND THE INFORMATION IT CONTAINS IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE, ARISING IN ANY WAY OUT OF THE USE OF THIS DOCUMENTATION, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any information or products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of information or products described herein, except as expressly agreed to in writing by NetApp. The use of this document, information, or the described products does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp. The products described in this document may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52.227-19 (June 1987).

No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.