

NetApp SolidFire VSS Hardware Provider Release Notes

Version: 2.0.2.1

3/14/2017

Copyright Information

Copyright © 1994-2017 NetApp, Inc. All Rights Reserved.

No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this document may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NetApp, the NetApp logo, AltaVault, ASUP, AutoSupport, Campaign Express, Cloud ONTAP, Clustered Data ONTAP, Customer Fitness, Data ONTAP, DataMotion, Fitness, Flash Accel, Flash Cache, Flash Pool, FlexArray, FlexCache, FlexClone, FlexPod, FlexScale, FlexShare, FlexVol, FPolicy, GetSuccessful, LockVault, Manage ONTAP, Mars, MetroCluster, MultiStore, NetApp Insight, OnCommand, ONTAP, ONTAPI, RAID DP, RAID-TEC, SANtricity, SecureShare, Simplicity, Simulate ONTAP, SnapCenter, Snap Creator, SnapCopy, SnapDrive, SnapIntegrator, SnapLock, SnapManager, SnapMirror, SnapMover, SnapProtect, SnapRestore, Snapshot, SnapValidator, SnapVault, StorageGRID, Tech OnTap, Unbound Cloud, WAFL, SolidFire, Element, Active IQ, SolidFire Helix and the helix design and other names are trademarks or registered trademarks of NetApp, Inc., in the United States, and/or other countries. All other brands or products are trademarks or registered trademarks of their respective holders and should be treated as such. A current list of NetApp trademarks is available on the web at <http://www.netapp.com/us/legal/netapptmlist.aspx>.

TABLE OF CONTENTS

- Introduction 1
 - Hardware Prerequisites 1
 - Software Prerequisites 1
 - Supported Configurations 2
- What's New in this Release 3
- Resolved Issues 3
- Known Issues and Workarounds 4
- Contacting SolidFire Active Support 5

Introduction

The SolidFire VSS Hardware Provider integrates VSS shadow copies with SolidFire snapshots and clones. The Provider runs on Microsoft® Windows® 2008 R2 and 2012 R2 editions and supports shadow copies created using DiskShadow and other VSS Requesters. A GUI-based configuration utility is provided to add, modify, and remove cluster information used by the SolidFire VSS Hardware Provider.

Utilizing VSS snapshot capabilities with the SolidFire VSS Hardware Provider ensures that snapshots are application consistent with business applications that use SolidFire volumes on a system. A coordinated effort between VSS components provides this functionality. SolidFire snapshots and clones minimize recovery time without affecting stability and performance and provide instant volume recovery.

Hardware Prerequisites

Component	Description
System processor	1.5 GHz (dual core recommended), Intel compatible 64-bit
System memory	Minimum 4 GB recommended
Free disk space required for installation	Minimum 5 MB required and recommended 100 MB
Networking	Ethernet ports for cluster communication and Ethernet ports for iSCSI or Fibre Channel ports
SolidFire cluster	A cluster of SolidFire nodes

Software Prerequisites

Component	Application	Description
Operating system	Microsoft® Windows® Server	Windows Server 2008 R2 64-bit Windows Server 2012 R2 64-bit Windows Server 2016 64-bit
	Microsoft® Hyper-V	Windows Server 2012 R2 64-bit Windows Server 2016 64-bit
.NET framework		4.5
SolidFire cluster		Element OS version 7.0 and later

Supported Configurations

VSS Hardware Provider configurations leverage directly connected SolidFire iSCSI or Fibre Channel volumes. Only the configurations described in the proceeding tables are supported.

Supported 64-Bit Operating Systems	
Windows Server 2008 R2	✓
Windows Server 2012 R2	✓
Windows Server 2016	✓
Hyper-V Server 2012 R2	✓
Hyper-V Server 2016	✓

The following OS and SQL Server combinations are supported.

OS/SQL Version	Stand Alone	Shared Storage Cluster	AlwaysOn Cluster
Windows Server 2008 R2			
SQL Server 2008 R2 SP3	✓	✓	
SQL Server 2012 SP2	✓		✓
SQL 2014		✓	✓
Windows Server 2012 R2			
SQL Server 2012 SP2	✓	✓	✓
SQL 2014	✓	✓	✓
SQL 2016	✓	✓	✓
Windows Server 2016			
SQL 2014	✓	✓	✓
SQL 2016	✓	✓	✓

What's New in this Release

The following new features and improvements are available in the SolidFire VSS Hardware Provider 2.0.2.1 release.

- Fibre Channel support:
 - Create shadow copies of connected volumes.
 - Unmask (import) shadow copy clones.
 - Mask (remove) clones.
- Expanded iSCSI support:
 - Create shadow copies of connected volumes.
 - Unmask (import) shadow copy clones.
 - Mask (remove) clones.
- VLAN support:
 - Create shadow copies of connected volumes.
 - Create iSCSI sessions that are connected to the cluster SVIP or one or more VLAN vSVIPs.
 - Disconnect iSCSI sessions that are connected to the cluster SVIP or one or more VLAN vSVIPs.
- Fibre Channel and iSCSI Multipathing support:
 - Discover Fibre Channel or iSCSI protocol endpoints for host connections.
 - Validate that a host is configured for multipath storage.
 - Multipathing configurations that use host NICs, vNICs, or multiple vSVIPs on the SolidFire cluster.
 - Creates multiple iSCSI sessions for multipathing to a shadow copy volume.
 - Log messaging for suboptimal or unsupported volume access group configurations.
- Improved event logging and tracing.
- Improved key encryption security for configuration data.
- Snapshot and clone prefix naming for all snapshots and clones created by the VSS Hardware Provider.
- Unique naming for each clone or snapshot.
- Configuration tool usability enhancements.

Resolved Issues

The following items have been corrected. The original ticket number is listed for reference.

Ticket #	Description
VSS-4	Using Windows 2012 R2 with Hyper-V role, VSS Hardware Provider v1.1.1.1 successfully creates a snapshot or clone on a SolidFire cluster but freezes waiting for metadata to be returned to the host.
VSS-115 (FB-20808)	When importing shadow copies, multiple iSCSI discovery portals might be created.
VSS-123 (FB-22676)	On a single occasion when performing a backup of a VM, the SolidFire VSS Hardware Provider did not remove the snapshot of a volume.

Known Issues and Workarounds

The following items are known issues that have been identified in the SolidFire system. Every effort is being made to design and provide solutions for the issues. The original ticket number is listed for reference.

Ticket #	Description	Details and Workaround
16135	VSS service fails with LUN resynchronization error during Resync operation in SQL shared storage cluster environment	This issue is applicable for SQL on a shared storage cluster. Perform one of the following procedures: 1. Disconnect the LUNs from the MSiSCSI initiator. 2. Reconnect the LUNs. 3. Make the disk <i>Online</i> manually from the Disk Management or DiskPart utility. 4. Restart the SQL Server service. Alternatively, perform the following in the Failover Cluster Manager: 1. Take the clustered disk offline on which resync is performed. 2. Bring the clustered disk online. 3. Restart the SQL service. The database is now accessible and the data is restored
16193	Resync of primary server snapshot on the secondary server is not supported in AlwaysOn cluster configuration	With AlwaysOn cluster configuration, the transportable snapshot that was created on a primary server (for database) cannot be used to restore the database once it is copied to a secondary server. This occurs because VSS Hardware Provider supports volume level restore and the storage LUNs mapped to the servers in Availability group are not shared. Resync of a transportable snapshot of one server to another is not supported.
16219	A VSS Writer error occurs when performing a Resync in an AlwaysOn cluster setup.	See the <i>Resync a Volume for AlwaysOn Clustered Setup</i> topic in the SolidFire VSS Hardware Provider User Guide.
VSS-16	When metadata is copied to a new host that is utilizing CHAP for volume access, attempts to import shadows will fail. The SolidFire VSS Hardware Provider leverages Volume Access Groups (VAG) for access. When a host uses CHAP, the Provider is unable to discover or mount new volumes offered by the VSS metadata file.	Configure hosts that will be used to expose or mount VSS shadow copies with volume access groups. Hosts currently configured to use CHAP can be converted to use volume access groups with minimal planned downtime. You can also mount a volume manually using CHAP.

Contacting SolidFire Active Support

If you have any questions or comments about SolidFire documents or products in general, contact SolidFire [support](#) or email support@solidfire.com.



1048 Pearl Street, Suite 250
Boulder, Colorado 80302

Phone: 720.523.3278

Email: info@solidfire.com

Web: www.solidfire.com

SolidFire Support: www.solidfire.com/support/

3/14/2017