



NetworkAppliance®

The evolution of storage.™

VFM™ (Virtual File Manager) 5.6 Troubleshooting Guide

Copyright © 2001-2005 NuView, Inc. All rights reserved.

Copyright © 2003-2005 Network Appliance, Inc. All rights reserved. Printed in the U.S.A.

No part of this book covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owners.

Software derived from copyrighted material of NuView, Inc. is subject to the following license and disclaimer:

Network Appliance and NuView, Inc. reserve the right to change any products described herein at any time, and without notice. Network Appliance and NuView assume no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by Network Appliance and NuView, Inc. The use and purchase of this product do not convey a license under any patent rights, trademark rights, or any other intellectual property rights of Network Appliance or NuView, Inc.

This product includes software developed by the Apache Software Foundation.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark information

NuView®, StorageX®, and associated logos are registered trademarks or trademarks of NuView, Incorporated. Other product and company names are trademarks of their respective owners.

NuView Incorporated, 738 Highway 6 South, Suite 850, Houston, Texas 77079
(www.nuview.com).

NetApp® and the Network Appliance design are registered trademarks of Network Appliance, Inc. in the United States, Canada, the European Union, and Japan. Network Appliance is a registered trademark of Network Appliance, Inc. in Monaco and a trademark of Network Appliance, Inc. in the United States and Canada. SnapMirror is a registered trademark of Network Appliance, Inc. in the United States.

VFM™ and the VFM logo are trademarks of Network Appliance, Inc.

Table of Contents

PREFACE	VII
CHAPTER 1 INTRODUCTION.....	9
CHAPTER 2 TROUBLESHOOTING	10
GENERAL PROBLEMS	10
DFS ROOT PROBLEMS	12
REPORT PROBLEMS	14
TARGET PROBLEMS	15
WINDOWS XP AND WINDOWS 2000 INCOMPATIBILITY PROBLEM	15
PROBLEMS CONNECTING TO THE STORAGEX SERVER SERVICE	16
PROBLEMS SELECTING A MONITORING AGENT	16
REPLICATION AND MIGRATION PROBLEMS	17
NETAPP FILER PROBLEMS	27
BROWSE NAMESPACE PROBLEMS	30
WINDOWS POWERED NAS OR WINDOWS STORAGE SERVER FILER IDENTIFICATION PROBLEMS	30
PROBLEMS RUNNING BATCH FILES	31
PROBLEMS RUNNING A POLICY	31
SNAPSHOT ACCESS POLICY PROBLEMS	33
PROBLEMS PRINTING TO PDF FILES	33
NAME OF MACHINE IS INCORRECT	34
PROBLEM TAKING SNAPSHOTS OF THE APPLICATION.....	34
PERMISSION BASED NAMESPACE POLICY PROBLEMS	34
PROBLEM INSTALLING A UNIX REPLICATION AGENT	34
PROBLEMS USING NTFS CHANGE JOURNAL	35
PROBLEM CONFIGURING THE OPENSSH PACKAGE ON SOLARIS	36
PROBLEM ACCESSING A UNIX MACHINE WHEN USING SSH	36
PROBLEMS REPLICATING DATA USING VSS SNAPSHOTS	37
APPENDIX A MIGRATION, REPLICATION, AND STATUS INDICATORS.....	39
MIGRATION TASK INDICATORS	39
REPLICATION STATUS MONITORING INDICATORS	39
STATUS INDICATORS	41
APPENDIX B EXCLUSION/INCLUSION EXAMPLES	45
APPENDIX C VFM DOCUMENTATION.....	49
GLOSSARY	51
INDEX	55

Preface

What the guide covers

This guide provides a list of problems that you might encounter when using VFM™ (Virtual File Manager) and explains how to fix the problems. It also provides a description of status indicators used as visual cues throughout VFM. The guide provides examples of exclusion and inclusion file formats.

The guide is divided into the following sections:

- **Chapter 1 Introduction** – Provides an overview of the document.
- **Chapter 2 Troubleshooting** – Provides troubleshooting information.
- **Appendix A Migration, replication, and status indicators** – Provides a description of migration task, replication status monitoring, and status indicators.
- **Appendix B Exclusion/inclusion examples** – Provides examples of exclusion and inclusion file formats.
- **Appendix C VFM Documentation** – Provides a list and description of the VFM documents.
- **Glossary** – Provides definitions of terms used in this guide.

Audience

This guide is for network administrators who are familiar with Windows NT®, Windows® 2000, Windows Server™ 2003, and DFS. It does not cover basic system or network administration topics.

Typographic conventions

- **Bold text** - Items on a dialog box or page on the VFM console that you are instructed to click.
- *<text in italics>* - Substitute the text within the greater than and less than symbols with the value requested.

Using the online help

- Certain icons appear to the left of a topic title to indicate that the information provided applies only to a specific operating system, type of DFS root, or data transfer protocol.

Icon	Description
	Indicates that the information applies only to DFS roots on Windows 2000 or Windows Server 2003, Enterprise Edition.
	Indicates that the information applies only to domain-based roots.
	Indicates that the information applies only to DFS roots on Windows Server 2003.



Indicates that the information applies only to CIFS data transfer.

- In the table of contents, a new topic is represented as a page with a red asterisk , and an entire section of new topics is represented as a book with a red asterisk .
- Definitions of new terms are available wherever they appear in help topics. The first time a new term appears in a help topic, it appears as a [green hyperlink](#).
- Context help contains detailed information about a dialog box or view, and might include links to related topics. Press **F1** or click **Help**.

Support

Contact NetApp® technical support, 24 x 7.

Support is either through the Web at <http://now.netapp.com> or by phone. See <http://www.netapp.com/support> for details.

Support phone numbers:

- 888 4-NETAPP (US and Canada)
- (1-888-463-8277)
- (408) 822-4700
- 800-44-NETAPP (EMEA/Europe)
- 800-800-0800 (Asia/Pacific)

Notes:

- You can also contact technical support by clicking **Support** on the **Help** menu.
- To get your product build number and license information, click **About Virtual File Manager** on the **Help** menu.

Enter new license key

Enter a new license key for the VFM client and server components when you want to extend the VFM evaluation period or when you purchase additional licenses from VFM.

1. Contact NetApp to request a new license key.
2. On the **Help** menu, click **About Virtual File Manager**.
3. Click **Edit Serial Numbers**.
4. In the License Type list, click the appropriate item.
5. If you selected "Evaluation" as the license type, type the new activation key.
6. If you selected "Full" as the license type, select a product number from the Product list and type the new activation key.
7. Click **OK**.

Chapter 1 Introduction

This guide provides a list of problems that you might encounter and explains about how to fix the problems. It also includes lists of status indicators used throughout the application. The following topics are included in this guide:

- Chapter 2 Troubleshooting
- Appendix A Migration, replication, and status task indicators
- Appendix B Exclusion/inclusion examples

Chapter 2 Troubleshooting

Start by checking the health of your VFM configuration and then browse the list of problems in the table below.

- Are the StorageX Server and StorageX Replication Agent services running on the machines where the VFM server or monitoring agent components are installed? Click **Agent Management** on the **Tools** menu to view the list of services installed on the system and ensure that the StorageX Server and StorageX Replication Agent services are enabled and started.
- Does sufficient free space exist on the drive containing "Documents and Settings" directories on the system where VFM is installed?
- Does the account used by the StorageX Server service have appropriate privileges to manage the selected DFS roots and access the source and destination of any data transfers?
- Does the account used to run the VFM console have administrator privileges on the system where it is installed?

General problems

If...	Then do this...
VFM seems slow to respond, or takes up a large amount of CPU.	• Check how many links are present in the DFS configuration. Larger configurations require VFM to gather additional information. • Verify that targets of links are reachable from the VFM console machine. • Verify that network browsing works correctly for regular Windows tools, such as Windows Explorer. • Check what level of status monitoring is enabled (root, link, storage) and what frequency monitoring is taking place. • Enabling the "show drives in physical views" option causes VFM to gather additional information and can slow operation, especially when target machines are not reachable from the VFM console machine.
You experience access denied errors while setting VFM system options.	The account running the VFM client must have permissions to write to the directory tree <i>All Users\Application Data\NuView\StorageX\GuiConsole</i> . Write permission for these directories are typically granted to members of the local administrators group and

If...	Then do this...
	the local power users group.
VFM reports an error about expired evaluation copy.	- Your evaluation copy expired. Contact your supplier to request an extension or to purchase a copy of VFM. - This error message can result when the currently logged in user attempting to run the VFM console is not a member of the administrators group on the local system.
VFM refuses to install.	- VFM currently supports installation only on Windows 2000 SP 2 or later. - Check whether the problem is installing MSDE. Microsoft KB article 315083 details various steps to take when troubleshooting a failed MSDE installation attempt.
You cannot drag-and-drop items out of Windows Explorer into VFM.	Items dragged to VFM must be network paths. You can map shares from remote machines as drives on your machine or address them as UNC paths. For local drives on your machine, you must address them as UNC paths (\\server\dir\).
You can only rearrange items displayed in Bold in the "Add Multiple Links" dialog box.	This is normal behavior. Use the VFM Logical View to make such changes when needed.
You encounter errors creating logical folders in your namespace	- Check that the permissions on the DFS root share grant the account running the VFM console the ability to make changes to the share. - Windows Server 2003 creates shares with default permissions of Everyone->Read. Windows 2000 creates shares with default permissions of Everyone->Full. The VFM server account must have permissions to write to the DFS root share to create logical directories in the namespace.
You changed your DFS configuration but client machines still access the old locations.	Clients cache referrals for a period of time. You can flush the client cache on Windows 2000 and later by performing one of the following actions: - Use the DFS tab of Windows Explorer Property dialog box to "clear history". - Run dfsutil with appropriate options on the client machine. - You must reboot clients running older operating systems, such as NT 4, Windows 98, or Windows 95, to clear the cache.
VFM shows the wrong date and time	Check whether you correctly set up remote shell

Troubleshooting

If...	Then do this...
for a NetApp filer message appearing in the Event View.	credentials on the filer. Normally, VFM uses RSH to communicate with NetApp filers and other non-Windows systems. When the remote shell credentials on the filer are not properly configured, VFM shows the filer message with the same date and time as the VFM server.
You see the error message "Network resource not found" when you try to upgrade the replication agent installed on the same machine as the VFM server.	• Check whether the VFM 5.5 server was uninstalled and the VFM 5.6 server was installed. • Before you upgrade the 5.5 replication agent, open a command prompt and change to the directory where the agent is installed and type the following command: <code>ReplicationAgent.exe -uninstall</code>

DFS root problems

If...	Then do this...
You do not see your roots in the VFM browse dialog box.	• Check whether network browsing is working correctly in Windows Explorer and correct any browsing problems. • Type the root name directly rather than browsing.
Changes made to domain roots (for example, creation or deletion) take a long time to appear in VFM.	Information about domain roots is hosted in Active Directory. There is a time lag while Active Directory replicates the changes. This time lag is affected by the Active Directory configuration.
You cannot create a DFS root using VFM.	• Check network connectivity by pinging the server the root is created on from the VFM machine. • Check that the account running VFM has appropriate privileges for the domain and servers where the domain-based root is being created or server where the stand-alone root is being created. • Check whether forward and reverse DNS lookups are accurate for the machine on which you want to create the root.

If...	Then do this...
You cannot add links to a DFS root.	• Check that the account running VFM has appropriate permissions for the DFS root being manipulated. • Check whether forward and reverse DNS lookups are accurate for the machine hosting the DFS root. • Verify that all root replica share names of a domain-based root match the name of the DFS root. This is particularly important for roots hosted on Windows Server 2003 systems.
Attribute sets are different between different types of roots.	The attributes that are available and capable of being set vary between NT4 roots, Windows 2000 stand-alone roots and domain-based roots. This is an artifact of DFS itself on these platforms and not a problem with VFM.
You have problems creating a domain-based root with replicas . After the domain-based root is created • It appears as a single replica root  • The status of the root is displayed as inaccessible 	• The creation of and operation on domain-based roots involves interactions with Active Directory. The Active Directory replication frequency affects how quickly changes appear in the VFM console. • Name resolution issues can affect the creation of domain-based roots. You might need to refer to the domain-based root by its fully-qualified domain name when accessing it when attempts to access it by its NETBIOS domain name are unsuccessful or result in inaccurate data. • Verify that all root replica share names of a domain-based root match the name of the DFS root. This is particularly important for roots hosted on Windows Server 2003 systems.
Morphed filenames appear in the namespace of domain root replicas	Do not enable FRS at the root level. The Microsoft DFS FAQ http://www.microsoft.com/windowsserver2003/techno/overview/dfsfaq.msp describes this symptom in more detail.
You get the following error when accessing a link contained in a consolidation root: "No network provider accepted the given path"	• Check whether the link is under a logical folder. You must configure links in consolidation roots directly under the root. They cannot be referenced under logical folders. This restriction applies only to consolidation roots.

Troubleshooting

If...	Then do this...
	• For more information about consolidation roots, see Microsoft Knowledge Base Article 829885.
You see the error message “The request is not supported” when attempting to create a DFS root.	This typically occurs when attempting to create a second DFS root on Windows Server 2003 Standard Edition server. Windows Server 2003 Standard Edition supports only one DFS root per computer. Windows Server 2003 Enterprise Server and Windows Server 2003 Datacenter support multiple DFS roots per server.

Report problems

If...	Then do this...
You experience errors attempting to run VFM reports.	The account running the VFM client must have permissions to write to the directory tree <i>All Users\Application Data\NuView\StorageX\GuiConsole</i> . Write permission for these directories are typically granted to members of the local administrators group and the local power users group.
Reports are slow to generate.	• Check the items under "General problems" for “VFM seems slow to respond...”. • Check whether you created a new report group when you created the report. Before VFM can create the report, the report group must gather the data. To cut down on report generation, create report groups to gather data before you assign and run reports based on the data gathered. • Create multiple reports instead of one large report. • Schedule report groups so that reports assigned to the report groups are available when needed for review.

Target problems

If...	Then do this...
VFM does not enumerate (browse) shares hosted on NetWare®, Win9x, and WinME systems.	These operating systems do not support the system calls required by VFM to gather information about their shares. You can add shares from these systems to your namespace by dragging their UNC paths from Windows Explorer and dropping them into any of the following: VFM Logical View, Add Link dialog box, Add Multiple Links dialog box.
When selecting targets for links, I do not see any entries in the Browse dialog box.	You might have browsed into a leaf directory and there are no subdirectories available at this level to which you can target links.
You see the error message "There were no targets for disaster recovery link on a disaster recovery policy."	Links that are members of disaster recovery policies must have at least two replicated targets. Only one target can be online. When the server where the active target becomes unavailable, VFM fails over the link to the replicated target and makes it the online target. For more information about failing over links see "Failover and replication options."
You see the error message "A new link was detected for the disaster recovery policy but the link cannot be added for the stated reasons."	• Check whether the root containing the link is hosted on NT4. NT4 does not support setting link target state. • Check whether the link is already in another disaster recovery policy. • See "Disaster recovery planning considerations" for more information.

Windows XP and Windows 2000 incompatibility problem

If...	Then do this...
Links for a stand-alone root running Windows 2000 do not appear when VFM is running on Windows XP.	Upgrade Windows 2000 to Service Pack 2 on the machine containing the stand-alone root.

Problems connecting to the StorageX server service

If...	Then do this...
The connection was refused by the StorageX Server Service	- The StorageX Server Service might have been stopped through the Windows Service Control Manager. Restart the StorageX Server Service. - The machine hosting the StorageX Server Service might not be reachable by the VFM console. Check your network connectivity and the machine hosting the StorageX Server Service. - Check whether the account configured for the StorageX server is in the local administrators group on the system where it is installed.
The VFM client reports access denied error attempting to connect to the VFM server.	Contact your VFM administrator to obtain access to the VFM server for your account.
The VFM client does not show updates	Check whether there is a loss of network connection between the VFM client and server. Clear this problem by exiting and reentering the VFM client.

Problems selecting a monitoring agent

If...	Then do this...
A monitoring agent is installed but does not appear as a choice in the Use the Monitor on list when configuring a client disaster recovery policy.	- Check that the machines on which the monitoring agent and the StorageX Server service are running have network connectivity with one another. - Check that the monitoring agent is configured with the correct hostname for the machine where the StorageX Server service is running. This value is stored in the registry at <i>HKLM\Software\NuView\StorageX\Services\Server\Primary</i> - Check that no firewalls are blocking TCP port 6001 between the monitoring agent and the StorageX Server service. Note: The following tables list the network ports used by DFS and VFM.

If...	Then do this...																		
	Network Ports Used by DFS																		
	<table><tr><th>Service Name</th><th>UDP</th><th>TCP</th></tr><tr><td>NetBIOS Datagram Service</td><td>138</td><td></td></tr><tr><td>NetBIOS Session Service</td><td></td><td>139</td></tr><tr><td>LDAP Server</td><td>389</td><td>389</td></tr><tr><td>Remote Procedure Call (RPC)</td><td></td><td>135</td></tr><tr><td>Server Message Block (SMB)</td><td>445</td><td>445</td></tr></table>	Service Name	UDP	TCP	NetBIOS Datagram Service	138		NetBIOS Session Service		139	LDAP Server	389	389	Remote Procedure Call (RPC)		135	Server Message Block (SMB)	445	445
	Service Name	UDP	TCP																
	NetBIOS Datagram Service	138																	
	NetBIOS Session Service		139																
	LDAP Server	389	389																
	Remote Procedure Call (RPC)		135																
	Server Message Block (SMB)	445	445																
	Network Ports Used by VFM																		
	<table><tr><th>Service Name</th><th>UDP</th><th>TCP</th></tr><tr><td>StorageX Server</td><td></td><td>6001</td></tr><tr><td>Replication Agent</td><td></td><td>6002</td></tr></table>	Service Name	UDP	TCP	StorageX Server		6001	Replication Agent		6002									
	Service Name	UDP	TCP																
	StorageX Server		6001																
	Replication Agent		6002																

Replication and migration problems

If...	Then do this...
VFM reports error messages indicating that the replication agent did not respond either in reports or in relation to replication tasks and your VFM server is installed on Windows 2000 Professional or Windows XP.	- Check the number of inbound connections on the machine hosting the VFM server. The VFM server accepts inbound connections from replication agents in response to commands sent from the server to the replication agents. If these connections in conjunction with other connections existing on the machine exceed the limits imposed by Windows 2000 Professional and Windows XP, the VFM server cannot receive responses from its replication agents and reports errors. - Microsoft Knowledge Base article 122920 documents these limits for Windows 2000, and Microsoft Knowledge Base article 314882 describes the limits in Windows XP. If the

Troubleshooting

If...	Then do this...
	connection count limits are an issue in your environment, run the VFM server on a Windows 2000 Server to avoid this problem.
VFM documentation mentions NFS file systems but you do not see them when you browse the network from your VFM console machine.	Windows clients need additional software to access NFS file systems. This additional software can be Microsoft tools, such as Services for UNIX® (either client or server), or various third-party NFS redirectors.
VFM reports an error when attempting to copy files when you can successfully copy them using Windows Explorer.	• VFM uses the backup read/write APIs to get the most accurate transfer of the source file and its associated attributes. Using these APIs requires specific privileges that your account might lack on the source or destination machines. Although Windows Explorer might copy the file data, attributes such as those governing security might be changed during the course of the transfer. • When copying files with summary information from Windows 2000 NTFS to NT4 NTFS, you must select the “allow loss of additional file streams” to perform the transfer. Windows 2000 NTFS creates a sparse file stream associated with the file when summary information is added to the file. NT4 NTFS does not support sparse files. • Check network connectivity between machines hosting the replication agent and those hosting the VFM server or monitoring agent.
StorageX Server service or StorageX Replication Agents fail to start.	• Check the Windows NT event log for errors related to startup failure • Check the Service Control Manager to see whether the StorageX Server or StorageX Replication Agent was stopped or its startup was disabled. • Check whether the account used by the service was removed from the domain. • Check whether the password was changed on the account used by the service. • Validate that the account and password information used by the service is correct. • Check whether the account used by the service has “logon as service” privilege enabled. • Check whether the StorageX Server or StorageX

If...	Then do this...
	Replication Agent is installed on the system. Note: When you install VFM, you are prompted for account and password for the VFM Server. The server caches password information using Windows 2000 LSA (Local Security Authority) facilities. The server uses the account and the cached password when deploying replication agents. You must use Service Control Manager To manually update information for the VFM server and deployed replication agents, click Agent Management on the Tools menu.
Deployment of replication agent fails	• Check whether the system being deployed to is up and reachable. This can be done by pinging it as well as using the net view command to view the shares that it publishes on the network. • Check whether there are domain trust issues preventing deployment. • Check whether there are network routing and infrastructure issues preventing network connectivity in both directions between the system hosting the server or monitoring agent and the system that hosts the replication agent. • Check whether the intended host of the Replication agent is being communicated over a VPN connection. ICMP packets typically do not travel over VPN connections. This restriction prevents the VFM server from correctly identifying the machine type of the intended host machine. It is also possible that the network administrator has restricted ICMP traffic on non-VPN connected machines. • Verify that the target system running one of the following platforms: Windows NT 4, Windows 2000, Windows Server 2003, or Windows XP. Agents cannot be pushed to other platforms. Note: If the machine on which you want to deploy a replication agent is running Windows XP SP 2, you must perform the following actions: 1. Disable the firewall on the machine on which you want to deploy the replication agent. 2. Restart the machine. • If the target system is running Windows NT 4, check whether MSXML3 is installed on the

If...	Then do this...
	system. You can do this by checking for the existence of the msxml3.dll in the system32 directory. MSXML3 is available for download from the Microsoft web site. • Check whether the normal admin\$ shares are published on the destination system. Try viewing the admin\$ share for the target system using Windows Explorer. • Check whether the account under which the StorageX Server service is running has privileges to write to the destination admin\$ share to install the replication agent. You can do this by using the Windows "run as..." facility to run Windows Explorer, and then browse the admin\$ share on the server. • Verify that there is space on the destination system to receive the replication agent. The replication agent requires approximately 700 KB to be installed. • Verify that the account under which the StorageX Server service is running has privileges to install and run as a service on the destination machine. • Check whether there are any firewalls between the system hosting the StorageX Server or StorageX monitoring agent services and the intended destination system for the replication agents that are blocking the port where the StorageX Server service listens (TCP port 6001). • Check whether any process is already listening on the port the StorageX Server and StorageX Replication Agent services use and thus preventing VFM from operating. • Check whether the Remote Registry Service (regsvc.exe) is started on the machine where the replication agent is to be deployed. Stopping this service interferes with the deployment and operation of the Replication Agent. • If the intended destination is a Microsoft Cluster Server Cluster, additional steps are required to configure the replication agent to run on the cluster. Contact support for this configuration information. Note: See the note in "Problem selecting a monitoring agent" for a list of network ports used by DFS and VFM.

If...	Then do this...
VFM cannot communicate with replication agents.	• Check whether there are any firewalls between the system hosting the StorageX Server or StorageX monitoring agent services and the intended destination system for the replication agents that are blocking the port where the StorageX Replication Agent service listens (TCP port 6002). • Check whether the console system or agent system is running a personal firewall, such as ZoneAlarm or BlackIce and whether the appropriate ports are open on it to allow communication. • Check whether any process is already listening on the port the StorageX Server and StorageX Replication Agent services use, thus preventing VFM from operating. • Check that the system hosting the replication agent can ping the system hosting the VFM server using the server name. Note: See the note in "Problem selecting a monitoring agent" for a list of network ports used by DFS and VFM.
VFM does not display full information about shares hosted on my filer.	Depending on the filer implementation, VFM might not support the detailed level of information provided by Windows systems. VFM displays as much information as can be obtained about storage targets.
Invalid security descriptor messages reported during migration operations.	• Check whether the source, the destination, and the machine hosting the DFS root are all in the same domain. If not, check whether trusts are set up appropriately among the systems. • Check whether the domain admin account under which the StorageX Server service was installed has administrator privileges on the source and destination of the replication. • Check whether the files for which the problem is reported are owned by a local account on the source machine. This can cause this error to be reported. • It is possible that the security descriptor on the file is invalid. When logged into the account used by the StorageX server service, check

Troubleshooting

If...	Then do this...
	whether you can view the security settings on the file from Windows Explorer. • Check whether the owner and primary group of the source files are valid on the destination machine. If the owner or primary group of a file is not present on the destination machine, warnings about invalid security descriptors can result. This can be the case if files and directories on the source machine have a local account as their owner or a local group as their primary group. You can use VFM replication options to control how local SIDs are processed during the replication process. • If the destination of the transfer is a NetApp filer, check the filer's /etc/messages file for any error messages indicating problems communicating with its domain controller.
Replication or migration operations produce error 1332 "No mapping between account names and security IDs was done."	• The files are owned by an unknown SID. Use Windows Explorer or another tool to assign ownership of the problem file to a known trustee. • This condition can arise if the account owning the file is removed from the system.
A replication or migration job is canceled after 60 minutes.	Check whether you have an evaluation license for VFM. Evaluation licenses enable you to copy only 60 minutes of data.
Replication or migration operations produce the following errors: • "Disk is full" • "The system cannot find the file specified"	Use the following checks to diagnose environmental problems: • Check whether space is available on the destination. • Check whether the quotas are not limiting the ability of the replication agent to write to the destination. This applies to NTFS quotas in Windows systems or qtree quotas in NetApp filers. • If the destination is hosted on a NetApp filer, check whether the /etc/messages file of the filer for any errors related to MAXDIRSIZE. It might be necessary to increase the value of this parameter on the filer if the destination will contain a very large number of files. • If the destination is hosted on a NetApp filer, check whether any files have UNC paths longer

If...	Then do this...
	than the limit of 256 characters set by Data ONTAP. This condition can occur if CIFS clients access data via shares of deeply nested subdirectories and replication is attempted from the root of a volume, causing a longer UNC path to be used in referencing the file on the filer. • If the destination is hosted on a NetApp filer, check whether the destination volume has sufficient nodes available to accommodate the files being transferred.
Replication and migration operations produce the following errors: • "Resource not found" • "Path not found" • "Source not found" • "Destination not found" • "Destination could not be created"	• Use the following checks to diagnose network problems: • Check whether the source server is accessible from the machine hosting the replication agent. For example, you can ping, net use, or browse for the machine in Microsoft Network neighborhood. • Check whether the destination server is accessible from the machine hosting the replication agent. For example, you can ping, net use, or browse for the machine in Microsoft Network neighborhood. • Check that the source and destination shares exist and are accessible from the machine hosting the replication agent. For example, you can try accessing source or destination shares via Windows Explorer. • Check whether the StorageX Server Service account is not explicitly denied share permissions on destination shares. • Check whether the StorageX Server Service account is in Local Administrators group of the source or destination server.
Replication and migration operations produce the following errors: • "Cannot delete source/destination. It is being used by another process" • "Cannot open source/destination. It is being used by another process"	Use the following checks to diagnose problems with locked files: • Check whether files or directories in question are being accessed by another application. Close all applications accessing the files or directories and retry data transfer. Files that are commonly locked include Outlook data files such as PSTs, database files used by Access, SQLServer, FoxPro, or Exchange. • Check whether nested data transfers are not in progress at the same time. The following example illustrates this problem: LinkA

Troubleshooting

If...	Then do this...
	references \\source\shareA and LinkB references \\source\shareA\folderB . LinkA and LinkB are source links in two different replication policies. Starting replication policies at the same time may lead to above errors. • Check whether the destination of the transfer is a filer, verify that any virus scanning software was disabled and retry the transfer. When enabled, virus scanning software can cause problems with locked files during large replications.
Replication and migration operations produce the following errors: • “Unable to delete a file. Access is denied” • “Unable to delete source. Access is denied” • “Unable to delete destination. Access is denied” • “Access to a directory or file is denied” • “Access is denied” • “Access to source is denied” • “Access to destination is denied”	Permission problems can be diagnosed by checking whether the following conditions are true for your environment: • Check whether the StorageX Server Service account is in the Local Administrators group of the source server. • Check whether the StorageX Server Service account is in the Local Administrators group of the destination server. • Check whether the StorageX Server Service account is not explicitly denied share permissions on the source or destination share. • If the source or destination is a NetApp filer, use the command <i>testdc</i> to verify that the system can communicate with domain controllers. • Check the filer’s /etc/messages file for errors related to communication with domain controllers.
There are warnings when you replicate or migrate data from Windows 2000 NTFS to NT4 NTFS.	The Windows 2000 version of NTFS supports a superset of the file information supported on NT4 NTFS. This means that not all the information associated with a file on a Windows 2000 NTFS file system can be transferred to an NT4 NTFS file system. VFM warns when this situation is encountered. This enables you to specify whether to carry out the operation.
VFM reports access-denied errors when attempting to transfer files to a filer and vscan is in use on the filer.	• Check whether the virus scanning software is operating correctly. It is possible to configure virus scanning software using the vscan interface to prevent any files from being written to the filer when the virus scanning software is inoperable. • Some conditions that can cause problems for virus scanning software include: changes to the account under which the virus scanning software runs or network connectivity problems between

If...	Then do this...
	the filer and the virus scanning host.
Files and directories on the source and destination have different permission settings.	• Check inherited permissions on the source and destination directory trees. • Check whether the data transfer was interrupted before it was completed. VFM manipulates directory permissions on the destination during the migration process to ensure it has sufficient permissions to write to tightly ACL-ed destination directories. After VFM has completed its work in a directory tree, the permissions are set to the actual permission intended for the destination. If the transfer is interrupted, it is possible that extra permissions may be present on destination directories because VFM was prevented from completing the permission-setting phase of the transfer.. • Check whether local trustee processing is enabled for the policy. Perform the following steps: 1. Right-click the policy and click Properties. 2. Click Replication Security. Note: Local trustee processing is not applicable when the source of a transfer is a Domain Controller. Domain Controllers do not host local SIDs.
You see the error 1130 "Not enough server storage is available to process this command."	Check whether the IRPStackSize parameter is set too low on the system reporting the error. Microsoft KB article 177078 describes the default values for this parameter and explains how to increase it through the registry for versions of Windows, including Windows Server 2003. http://support.microsoft.com/default.aspx?scid=kb;en-us;177078
You have problems transferring data using the NFS protocol	• Check whether the machine where the UNIX replication agent is running can resolve the name of the NFS server you are trying to contact. • Login to the machine where the UNIX replication is installed and ping the NFS server. • In a mixed Windows and UNIX environment, always use the fully qualified DNS name. • Login to the NFS server and run "exportfs" with no arguments. Check whether the path you are

If...	Then do this...
	trying to contact or one of its parent directories appears with the rights you expect. • Check the exports file on the NFS server you are trying to contact. This file is found in the following locations: • Linux - /etc/exports • Solaris - /etc/dfs/dfstab • NetApp - <the name of the root volume>/etc/exports OR /etc/exports • Check whether the path you are trying to contact or one of its parent directories is in the exports file. If the path exists, check whether the rights granted are correct. To clarify the instructions that follow, VFMmachine is used to represent the machine communicating with the UNIX server. The machine can be the VFM server or UNIX replication agent. The entry for the machine is its IP address or fully qualified DNS name. • Linux - Search for an entry that contains *(rw) or VFMmachine(rw) Note: Within the parentheses, there can be other rights, however, it is very important that "rw" (read/write) access is granted. • Solaris and NetApp - Entries are separated by commas. Search for the entry "rw", "rw=VFMmachine", or "root=VFMmachine" Note: Make sure that "ro" or "ro=VFMmachine" are not specified. The VFM machines might appear in a colon-separated list with other machines. • Normally, VFM uses root (uid 0). You can specify a different uid for a UNIX machine or filer. When the uid is not root, the replication agent might not be able to copy some security information and reports data transfer failures. To suppress these error reports, perform the following actions: 1. Right-click the policy that contains the UNIX machine or filer and click Properties. 2. Click Security Replication. 3. Select Allow loss of security

If...	Then do this...
	information. 4. Click OK. - When an export is used as root (uid 0), special entries are required in the exports file. Linux - The VFM machine entry <u>must</u> include "no_root_squash" or "anonuid=0" (for example, "rw,no_root_squash"). Make sure that "root_squash" is <u>not</u> specified. Solaris and NetApp - When the VFM machine is not given explicit "root" access, the entry "anon=0" must be included in the exports file. Note: After changing the exports file, run the following commands: <pre>exportfs -ua exportfs -a</pre> To check what the NFS machine is exporting, execute the command exportfs. - Check The UNIX security mode-bit rights on the NFS machine and compare them with the rights of the files you are trying to access. - For NetApp filers, check whether the volume/qtree is set to use UNIX security. If the security mode is NTFS, VFM cannot perform attribute settings on the filer volume or qtree. Perform the following actions: - The UNIX user must be mapped to an NTFS user in the file /etc/usermap.cfg. - Select "Allow loss of security information" in the properties of the policy. This suppresses error messages reported by the UNIX replication agent.

NetApp filer problems

If...	Then do this...
NetApp filers are identified as generic machines.	Check network connectivity between the VFM console machine and filer. VFM provides a batch file that you can pass arguments to check the filer. The

Troubleshooting

If...	Then do this...
	FilerCheck.bat file is in the Tools\FilerCheck directory in the VFM server installation directory. At a command prompt type Filercheck <filer> <username:password> <community name>, where "filer" is the name or IP address of the filer, "username:password" is the username and password used to access the filer through rsh, and "community name" is the SNMP community name used to access the filer through SNMP. Filercheck performs the following checks: • Checks whether the current account has administrator privileges on the filer or vFiler™. The lack of these privileges prevents accurate identification. • Checks whether the current account can access \\filer\IPC\$ through a “net use” command. If IPC\$ cannot be accessed, VFM cannot complete the filer identification process. • If you have access to an account with administrator privileges on the filer, you can explicitly map a drive on your VFM console machine to the \\filer\c\$ share using that account to administer the filer through VFM.
NetApp filers are identified as vFilers rather than as filers	Check that SNMP is enabled on the filer and that the community string used by VFM to communicate with the filer is correct. VFM uses “public” as the default community string. You can override this through the Tools>Options dialog box, as well as on a per-machine basis through the machine properties dialog box for each specific machine. VFM provides a batch file that you can pass arguments to check the filer. The FilerCheck.bat file is in the Tools\FilerCheck directory in the VFM server installation directory. At a command prompt, type Filercheck <filer> <username:password> <community name>, where "filer" is the name or IP address of the filer, "username:password" is the username and password used to access the filer through RSH, and "community name" is the SNMP community name used to access the filer through SNMP.
FilerView does not appear as expected in the Manage tab	Check whether you can browse to http://filer/na_admin using Internet Explorer on the VFM machine to get to the FilerView Web user interface.
Attempting a filer management	• The NetApp filers are under an extremely

If...	Then do this...
operation, such as creating or initializing a SnapMirror® function or showing a filer in the Admin View causes the following errors: • "Device command didn't report an output" • "SnapMirror is too busy, please try again later"	heavy load. Retry the operation when the load on the filers has decreased.. • Check whether the /etc/snapmirror.conf file is 0 bytes. If snapmirror.conf does not contain the normal comment showing when the file was generated by Data ONTAP™ software, add a placeholder comment or delete the file. • Check the file /etc/messages on the filer for SnapMirror-related error messages or RSH-related error messages. Note: VFM does not support automatic creation of SnapMirrors on separate network interfaces than the primary interface used by VFM to communicate with the filers.
Refreshing filer information or filer event information results in "access denied" errors.	VFM provides a batch file that you can pass arguments to check the filer. The FilerCheck.bat file is in the Tools\FilerCheck directory in the VFM server installation directory. At a command prompt type Filercheck <filer> <username:password> <community name>, where "filer" is the name or IP address of the filer, "username:password" is the user name and password used to access the filer through RSH, and "community name" is the SNMP community name used to access the filer through SNMP. Filercheck performs the following checks: • Checks whether the current account has administrator access to the c\$ share on the filer. To manually check access, try to browse the c\$ share using Windows Explorer (for example, \\<filename>\c\$). • Checks whether the current account has administrator privileges on the filer or vFiler. Lack of these privileges results in "access denied" errors. • If RSH reports: "<filename>: Permission denied. RSH: cannot establish connection", the filer is configured with the administrator name and possibly the administrator password. • If rsh reports something like: "NetApp Release 6.3: Wed Aug 7 23 : 04 : 57 PDT 2002", the RSH command succeeded against the filer. If the filer is configured with a user name and password, you must enter the user name and password on the Filer Account tab of the machine's properties in

If...	Then do this...
	VFM. If the RSH check is indeterminate, you can use telnet to check whether the filer is prompting for a user name and password. From a command prompt on the VFM client machine, telnet to the filer and check whether the filer prompts for a user name and password.

Browse namespace problems

If...	Then do this...
Attempts to browse or manage the DFS namespace yield "RPC server not available" error messages.	Check whether the DFS service is running on the machine hosting the DFS root.
Attempts to browse the namespace yield "access denied" errors.	Check whether the current account has privileges to access the share hosting the DFS root, as well as to the root itself in the case of domain roots. If access denied errors are reported when attempting to browse folders in the namespace, check the permissions of the shares hosting these folders as well as the permissions on the folders themselves. When accessing resources through the namespace, the credentials used for the access are those used when the user initially accesses the namespace. This can cause problems in environments where users typically use explicit credentials to map network drives.

Windows powered NAS or Windows storage server filer identification problems

If...	Then do this...
Windows Powered NAS or Windows Storage Server filers are being identified as generic machines.	Check whether the current account has administrator privileges on the Windows Powered NAS or Windows Storage Server machine by using RegEdit.exe to connect to the filer's registry. Inability to open the filer's registry prevents VFM from accurately identifying it as a Windows Powered NAS or Windows Storage Server filer.

Problems running batch files

If...	Then do this...
Problems are encountered trying to run batch files configured to run with VFM storage policies.	• See "Running batch files" for information about running batch files in VFM. • See "Batch files" for detailed information about the example scripts provided by VFM. • Save your BAT file log to a text file. You can examine the contents of the text file to diagnose potential problems. Adding a line such as, <code>"echo %date% %time% The arguments passed from server are: %* >> Decision.txt"</code> will record all the arguments passed to your BAT file along with the date and time that the script ran. This information is appended to the file "Decision.txt" located in the directory where the BAT file is running.
You get the following error when you know that you correctly typed the path of the batch file: "Script was not found"	Check whether the script path contains spaces. If the path contains spaces, you must enclose the path in double quotes. If you browse for the script, VFM encloses the path in double quotes for you.

Problems running a policy

If...	Then do this...
You see the following error messages: • The namespace backup policy failed. • Manually running the namespace	• Check whether the account running VFM has appropriate permissions for the DFS root being manipulated. • Check whether VFM can communicate

Troubleshooting

If...	Then do this...
backup policy failed	with the DFS root. Check network connectivity by pinging the server where the root is located from the VFM machine. • Check whether there is a problem communicating with the VFM database.
You see the following error messages: • The server disaster recovery policy was unable to retrieve the active link information • The server disaster recovery policy failed to activate the primary server target for the link • The server disaster recovery policy failed to activate the secondary server target for the link	• Check whether VFM can communicate with the servers that contain the link targets. • Check whether the account running VFM has appropriate permissions for the DFS root being manipulated. • Check whether VFM can communicate with the DFS root. Check network connectivity by pinging the server where the root is located from the VFM machine.
The server availability policy fails	• Check whether the active and standby server can communicate. • Check whether the account running VFM has appropriate permissions to access the active and standby servers. • Check whether the VFM service is running.
You see the following error messages: • The policy scan for the storage load balancing policy encountered problems • Failed updating DFS links for a task in the storage load balancing policy	• Check whether the account running VFM has appropriate permissions for the DFS root being manipulated. • Check whether VFM can communicate with the DFS root. Check network connectivity by pinging the server where the root is located from the VFM machine. • Check whether VFM can communicate with the storage resources. • Check whether the account running VFM has appropriate permissions to access the storage resources.

Snapshot access policy problems

If...	Then do this...
The restore operation is not working.	Check whether the volume hosting the files has the <i>.snapshot</i> directory visible. VFM cannot restore data hosted on a volume where the <i>.snapshot</i> directory is not visible.
You cannot view files on the Explorer tab of a snapshot access policy.	- The <i>.snapshot</i> directory on the volume hosting the data might not be visible. Make sure that the operating system is configured to show hidden files. - To access snapshots from CIFS clients, type the following command on a command prompt: <code>\\<filename>\<share>\.snapshot</code> Where "filename" is the name of the filer you are using and "share" is the name of the share you want to access.
You encounter "network resource not found" errors when attempting to use the SnapRestore™ function to retrieve items from the SnapShot Access Namespace Explorer view.	Check to see whether there is a mismatch between the exact local path on disk of the shared directory and the local path entered when creating the path. These two items must match exactly, including upper/lower case of the path components, for SnapRestore to work. You can correct this by removing and re-creating the share using the exact name of the local path and re-creating your SnapShot access policy.

Problems printing to PDF files

If...	Then do this...
Cannot print from VFM to PDF files.	- Check whether VFM was upgraded using terminal services. - You need to upgrade from the machine console and not through terminal services.

Name of machine is incorrect

If...	Then do this...
The name of a machine in the Physical View is incorrect.	Check whether DNS forward and reverse lookups are configured correctly for the machine.

Problem taking snapshots of the application

If...	Then do this...
You see "access denied" errors while trying to take a snapshot of the application.	Check the permissions on the snapshot save location (both share and local directory) to ensure that both the account under which MSDE and the account under which the VFM server are running have permission to write to the snapshot save location.

Permission based namespace policy problems

If...	Then do this...
Links were not created when you ran the policy.	Check whether you tried to add multiple links with the same name. If you selected domains to search for resources and the domains contain groups with the same name (for example, domain1\sales and domain2\sales), make sure that you select a template that sorts by domain, such as Domain-Group Name-Machine-Shares, Machines-Domain-Group Name-Shares, or Domain-Group Name-Shares. You cannot create links with the same name under the root or a logical folder of the namespace.

Problem installing a UNIX replication agent

If...	Then do this...
You get the following error message while	Check whether the file system where you are

If...	Then do this...
trying to install a UNIX replication agent: - On Solaris: pkgadd: ERROR: Unable to make directory </usr/local/URA> - On Linux: error: unpacking of archive failed on file /usr/local/ura/bin: cpio: mkdir failed - No such file or directory	installing the replication agent is mounted read-write. The file system where a replication agent is installed must be mounted read-write.

Problems using NTFS Change Journal

If...	Then do this...
You see one of the following error messages: "Change Journal could not be used because this is the first time the job ran." "Change Journal could not be used because it is not active and auto-enabling is not permitted." "Change Journal could not be used due to an unexpected failure."	- The NTFS Change Journal is supported on Windows 2000 NTFS which is available on Windows version 2000 and later of the Windows operating system. - When you enable the NTFS Change Journal on a volume, the size of the volume is used to determine the amount of space dedicated to the change journal. For each 50 GB of space on the volume, 128 MB is assigned for use by the change journal up to a maximum of 10 GB. On Windows 2000 SP2 or below, the amount of space dedicated to the change journal is always 128 MB, regardless of the size of the volume. - Use of this option requires that VFM deploy a replication agent on the machine where the source data resides and enable the change journal on the NTFS volume hosting the source data. The VFM machine properties dialog enables you to control whether the replication agent can be deployed to a machine and whether VFM can enable the NTFS change journal for volumes on the machine. - Use of this option means that changes made on the source are replicated to the destination and changes made on the destination are not overwritten by data from the source unless the corresponding file on the source changes as well. This differs

Troubleshooting

If...	Then do this...
	from standard VFM replication, wherein changes made on the destination are detected and overwritten with data from the source. • In cases where the change journal wraps, VFM must perform a full scan of the source and destination to determine what files need to be transferred. • When both Delete orphaned files in destination folders and Use NTFS Change Journal are selected, VFM deletes a destination file when its corresponding source file is deleted. If a new file is added to the destination, the file is <u>not</u> deleted unless the file is contained in a directory that is deleted on the source.

Problem configuring the OpenSSH package on Solaris

If...	Then do this...
You see the error message "Privilege Separation user sshd does not exist"	Edit the /etc/passwd file and add the following line at the bottom of the file: <pre>sshd:x:74:74:Privilege-separated SSH:/var/empty/sshd:/sbin/nologin</pre> Note: The command should not have line breaks. It should be written in one line.

Problem accessing a UNIX machine when using SSH

If...	Then do this...
You are prompted for a password when you access a UNIX machine when VFM is configured to use SSH	• If you generated a SSH2 (RSA) or SSH2 (DSA) key, check whether you created the file "authorized_keys2." See Step 3 in "Copy the public key to a

If...	Then do this...
	UNIX machine." • Check whether you generated the keys without a password or passphrase. See Step 5 in "Generate a key-pair." • Check whether OpenSSH is installed on the UNIX machine. See "Install and configure OpenSSH on Solaris" or "Install and configure OpenSSH on RedHat" for detailed instructions about how to install OpenSSH. • Make sure that you have the appropriate permissions. See Step 6 in "Copy the public key to a UNIX machine."

Problems replicating data using VSS snapshots

If...	Then do this...
Time-out errors occur in volume shadow copy service writers, and shadow copies are lost during backup of high input/output activity	Apply a hot fix update to the Volume Shadow Copy service (VSS) for Microsoft Windows Server 2003 which is available at the following Web site: http://support.microsoft.com/kb/833167#8 The update addresses this and other known VSS problems.

Appendix A Migration, replication, and status indicators

Migration task indicators

The following list specifies status indicators that are used as visual cues.

Source Share	Description
	The task is scheduled to be processed.
	User action is required.
	A task was completed successfully or was canceled.

Replication status monitoring indicators

The following list specifies status indicators that are used as visual cues.

Replication policy	Description	Example
	Replication is in progress or completed.	
	Warning - A link in the policy is in an abnormal state. - A target in the policy is in an abnormal state	- Replicas could be offline. - Access permissions prevent VFM from completing some aspects of a link. - A target might be unreachable due to network or machine problems. - Access permissions on a target might prevent VFM from accurately assessing the state of the target.
	Error - VFM detected a serious problem.	- The policy has no source link or no destination link. - The last synchronization attempt failed. - The source link has more than one target.
	Unknown - VFM cannot	

Troubleshooting

Replication policy	Description	Example
	determine the state information for one or more items in the policy.	

Target	Description	Example
	In progress - Data is currently being moved to the target.	
	Completed - Data move to the target was completed successfully.	• All files were copied. • No files needed to be copied.
	Warning - Data move to the target encountered some failures.	• Some files failed to be copied. • No files were copied, but some failed to copy due to sharing violations. • All files were copied, but some files had warnings.
	Error - The target is in an abnormal state.	• The target might be unreachable due to network or machine problems. • Access permissions on the target might prevent VFM from accurately assessing the state of the target. • There were problems with a DFS root. • No files were copied for reasons other than sharing violation.
	Unknown - VFM cannot determine the state information for the target.	

Status indicators

The list below specifies status indicators that are used as visual cues for the following items:

DFS root	Description	Example
 Note: Single and replicated DFS roots have the same status symbols.	Online	
	Warning - VFM detected that one or more elements being monitored are not operating correctly.	- A DFS link has some replica shares that are unavailable. - Access permissions prevent VFM from monitoring the status of some portion of the root. - FRS is enabled for some, but not all of the replicas for this domain-based root.
	Error - VFM detected a serious problem.	- The internal data structure of the DFS root is corrupted. - All the replicas for a link are offline. - The DFS root is offline or does not respond to queries.
	Unknown - VFM cannot determine the state information for one or more DFS elements.	

DFS Link	Description	Example
 Note: Single and replicated DFS links have the same status symbols.	Online	
	Warning - VFM detected that one or more shared folder replicas being monitored are not operating correctly.	- A DFS link has some replica shares that are unavailable. - Access permissions prevent VFM from monitoring the status of some portion of the link. - FRS is enabled for some, but not all of the replicas for this link in a domain-based root.

Troubleshooting

DFS Link	Description	Example
		A single-target link is a member of a disaster recovery policy.
	Error - VFM detected a serious problem.	All the replicas for a link are unavailable.
	Unknown - VFM cannot determine the state information for one or more replicas.	

Shared folder	Description	Example
	Online	
	Warning - VFM detected that the shared folder being monitored is not operating correctly.	- The shared folder is unavailable. - Access permissions prevent VFM from monitoring the status of the shared folder.
	Error - VFM detected a serious problem.	The shared folder is offline.
	Unknown - VFM cannot determine the state information of the shared folder.	

Logical folder	Description	Example
	Online	
	Warning - VFM detected that the folder being monitored is not operating correctly.	- The shared folder is unavailable. - Access permissions prevent VFM from monitoring the status of the shared folder.
	Error - VFM detected a serious problem.	The shared folder is offline.
	Unknown - VFM cannot determine the state information of the folder.	

Appendix A Migration, replication, and status indicators

Machine	Description	Example
 Note: All the machines have the same status symbols.	Information about the machine was updated without errors or Unknown - The machine was not refreshed.	
	Refreshing - Information about the machine is being updated.	
	Error - VFM detected a problem.	• There is a problem refreshing the server information (for example, comment, IP address or platform) • There is a problem refreshing the NetApp filer information (for example, volume or SnapMirror) • There is a problem refreshing the NetApp filer events.

Volume	Description	Example
	Information was updated without errors or Unknown - The volume was not refreshed.	
	Refreshing - Information about the volume is being updated.	

Qtree	Description	Example
	Information about the qtree was updated without errors or Unknown - The volume was not refreshed.	
	Refreshing - Information about the qtree is being updated.	

Troubleshooting

Export	Description	Example
	Online	
	Warning - VFM detected that the export being monitored is not operating correctly.	• The export is unavailable. • Access permissions prevent VFM from monitoring the status of the export.
	Error - VFM detected a serious problem.	The export is offline.
	Unknown - VFM cannot determine the state information of the export.	

VFM server and monitoring agent	Description	Example
	No problems were detected	
	Warning - VFM server is in an unknown state.	
	Error - VFM detected a problem.	• The database data file is full. • The database log file is full.

Appendix B Exclusion/Inclusion Examples

The following table provides a list of valid exclusion and inclusion formats and includes an explanation for each format. Type multiple exclusions and inclusions delimited by double quotes.

Item	Format	Description
1	*	Match everything (files and subfolders) beneath the directory.
2	*.*	Match everything (files and subfolders) beneath the directory.
3	\ (Windows) / (UNIX)	Match everything (files and subfolders) beneath the directory.
4	* (Windows) /* (UNIX)	Match everything (files and subfolders) beneath the directory.
5	*.* (Windows) /*.* (UNIX)	Match everything (files and subfolders) beneath the directory.
6	*.tmp	Match files or folders with an extension of "tmp".
7	listing???.txt	Match files or folders whose name begins with "listing", followed by three characters, and whose file extension is "txt".
8	listing.txt	Match files or folders named "listing.txt".
9	listing	Match files or folders named "listing" Notes: • If you use this example in an exclusion list and "listing" is a directory, the directory and everything under it is excluded. • If you use this example in an inclusion list and "listing" is a directory, only "listing", without its contents, is included; "listing" is included as an empty folder.
10	\listing (Windows) /listing (UNIX)	Match files or folders named "listing". Notes: • If you use this example in an exclusion list and "listing" is a directory, the directory and everything under it is excluded. • If you use this example in an inclusion list and "listing" is a directory, only "listing", without its contents, is included; "listing" is included as an empty folder.

Troubleshooting

Item	Format	Description
11	listing\ (Windows) listing/ (UNIX)	Match folders named "listing". Notes: - If you use this example in an exclusion list, the "listing" folder and everything under it is excluded. - If you use this example in an inclusion list, the "listing" folder and its contents are included.
12	\listing\ (Windows) /listing/ (UNIX)	Match folders named "listing". Notes: - If you use this example in an exclusion list, the "listing" folder and everything under it is excluded. - If you use this example in an inclusion list, the "listing" folder and its contents are included.
13	listing\file.txt (Windows) listing/file.txt (UNIX)	Match files or folders named "file.txt" that are in a folder named "listing". Notes: - If you use this example in an exclusion list and "file.txt" is a directory, the directory and everything under it is excluded. - If you use this example in an inclusion list and "file.txt" is a directory, only "file.txt", without its contents, is included; "file.txt" is included as an empty folder.
14	listing*\file.txt (Windows) listing/*\file.txt (UNIX)	Match files or folders named "file.txt" that are in a folder that is ultimately contained in a folder named "listing". Notes: - If you use this example in an exclusion list and "file.txt" is a directory, the directory and everything under it is excluded. - If you use this example in an inclusion list and "file.txt" is a directory, only "file.txt", without its contents, is included; "file.txt" is included as an empty folder.
15	\\saturn\archive\file.txt (Windows) Moria:/root/file.txt (UNIX)	Match the file or folder whose path is "\\saturn\archive\file.txt" or Moria:/root/file.txt. Notes: - If you use this example in an exclusion list and "file.txt" is a directory, the directory and everything under it is excluded. - If you use this example in an inclusion list and "file.txt" is a directory, only "file.txt", without its contents, is included; "file.txt" is included as an empty folder. - Use of fully qualified paths is not recommended,

Appendix B Exclusion/Inclusion Examples

Item	Format	Description
		especially for disaster recovery and replication manager policies. In these cases, the inclusion or exclusion list might be used with multiple source paths that might lead to unintended results.
16	\\saturn\archive\listing (Windows) Moria:/root/listing (UNIX)	Match the file or folder whose path is "\\saturn\archive\listing" or "Moria:/root/listing." Notes: • If you use this example in an exclusion list and "file.txt" is a directory, the directory and everything under it is excluded. • If you use this example in an inclusion list and "file.txt" is a directory, only "file.txt", without its contents, is included; "file.txt" is included as an empty folder. • Use of fully qualified paths is not recommended, especially for disaster recovery and replication manager policies. In these cases, the inclusion or exclusion list might be used with multiple source paths that might lead to unintended results.

When creating inclusion or exclusion lists, remember the following points:

- Exclusion terms are processed before inclusion terms. Files or directories matching an exclusion term are not processed further and cannot be included by a subsequent inclusion term.
- To include a subdirectory and its contents, specify a backslash “\” (Windows) or a forward slash “/” (UNIX) after the directory name.
- To include just a subdirectory and not its contents, omit the trailing backslash or forward slash.
- To exclude a subdirectory and its contents, the trailing backslash or forward slash is optional (The subdirectory and its contents are excluded whether or not the trailing backslash or forward slash is present).
- When you specify “delete orphans” for a transfer, the inclusion and exclusion lists affect how VFM handles orphan files on the destination.
 - Orphan files on the destination that match the exclusion term are not deleted, while orphan files not matching the exclusion term are deleted.
 - Orphan files on the destination that match the inclusion term are deleted.

Appendix C VFM Documentation

The following table lists the VFM guides. The list is arranged in ascending order by document title.

No.	Title	File name	Contents
1.	Advanced Configuration and Techniques	AdvancedConfig.pdf	• Explains how to use VFM to configure security permissions • Explains how to manage replication and monitoring agents • Explains how to run batch files in policies and reports • Explains how to make the VFM server highly available
2.	Data Lifecycle Automation Policies Guide	DataLifecyclePolicies.pdf	Explains how to create and manage archival migration policies to optimize storage.
3.	Data Movement Policies Guide	DataMovePolicies.pdf	• Explains how to transfer CIFS and NFS data by creating migration and replication policies • Explains how to transfer data between NetApp filers by creating SnapMirror policies • Explains how to load balance Windows servers by creating storage load balancing policies
4.	Disaster Recovery Policies Guide	DRPolicies.pdf	Explains how to make data highly available by creating client, filer, and server disaster recovery policies
5.	Getting Started Guide	GettingStarted.pdf	A tutorial to get you started using VFM. It explains how to install VFM and steps you through the process of creating a logical namespace, making the namespace highly available, making data highly available, transferring CIFS and NFS data, creating multiprotocol namespaces, virtualizing user home directories, and backing up data and the namespace.
6.	Manage Physical	PhysicalResources.pdf	Explains how to use VFM to work

Troubleshooting

No.	Title	File name	Contents
	Resources Guide		with NetApp filers, set replication properties, and work with Windows and UNIX machines
7.	Namespace Guide	Namespace.pdf	Explains how to create a DFS namespace (roots, links, and link targets), namespace creation, permission based, namespace availability, multiprotocol namespace, home folder, and namespace backup policies
8.	Reports Guide	Reports.pdf	Explains how to create and publish reports
9.	Snapshot Policies Guide	SnapshotPolicies.pdf	Explains how to use VFM to manage snapshots on NetApp filers using snapshot access and snapshot scheduling policies
10.	Troubleshooting Guide	Troubleshooting.pdf	• Includes diagnostic information, such as troubleshooting, event IDs, migration, replication, and status indicators • Provides examples of file exclusions and inclusions

Glossary

A

ACE: Access Control Entry, an entry in an Access Control List.

ACL: Access Control List, a list associated with a file that contains information about which users or groups have permission to access or modify the file.

Alternate volume: SEE Replica.

C

Child node: SEE DFS link.

CIFS: Common Internet File System. A file-sharing protocol based on the Microsoft Server Message Block (SMB). It enables you to share file systems over the Internet and Intranet. The CIFS protocol is used primarily for file sharing by Windows platforms.

Client: The user interface component of the application.

Consolidation DFS root: A special stand-alone DFS root that has its configuration information stored locally on a member server. The root must be hosted on Windows Server 2003.

D

Dependencies: The servers, drives, and shared folders that together contain the data published through the DFS namespace

DFS: Microsoft Distributed File System consists of software residing on network servers and clients that transparently links shared folders on different file servers into a single namespace for improved load balancing and data availability. NOTE: This should not be confused with Transarc's DFS product, which is a separate distributed file system product that is not interoperable with the Microsoft product.

DFS branch: SEE Shared folder.

DFS leaf: SEE Shared folder.

DFS link: Located under the DFS root. Forms a connection to one or more shared folders, DFS links, or another DFS root. NOTE: In Windows NT 4 terminology, this is referred to as a child node, a junction point, or an inter-DFS link.

DFS namespace: The logical view of shared file resources seen by users.

DFS path: A UNC path starting at a DFS root. Stand-alone DFS paths are rooted at a stand-alone root, while domain-based paths are rooted at a domain-based DFS root.

DFS root: The share at the top of the DFS topology. The starting point for the DFS links and shared folders that make up the DFS namespace.

DFS topology: Overall logical hierarchy of a distributed file system, including elements such as roots, links, shared folders, and replica sets.

DFS tree: The consolidated DFS view provided by the application, which includes the Admin View, Logical View, Physical View, and Reports.

Troubleshooting

DFS volume: SEE Shared folder.

Domain-based DFS root: A DFS root that has its configuration information stored in Active Directory. The root can have multiple root targets, which offers fault tolerance and load sharing at the root level.

E

Export: SEE NFS export

F

Fault-tolerant DFS: SEE Domain-based DFS root

FQDN: Fully-qualified Domain Name. A host, domain name, and a top-level domain. For example, www.nuview.com is a fully-qualified domain name where www is the host, .nuview is the second-level domain, and .com is the top-level domain.

FRS: Microsoft File Replication Service.

G

GID: Group Identification Number. A unique number assigned to identify a group of users in UNIX environments.

I

Inter-DFS link: SEE DFS link.

J

Junction point: SEE DFS link.

K

Key-pair: Consists of a public key and a corresponding private key. It is safe to distribute a public key, but a private key must be kept secret.

L

Link target: A DFS link can have as targets: 1 to N shared folders, OR 1 to N stand-alone DFS paths, OR only 1 domain-based DFS path.

M

Migration candidates: Items that match migration criteria in an archival migration policy. You can select which items you want to migrate. Items not selected for migration are automatically added to the exclusion list of the archival migration policy.

Migration tasks: Items to be migrated during a scheduled migration or manually at any time.

Monitoring agent: The component that can be installed to evaluate storage policies from a

different machine than the one where the application server is installed.

N

NFS: Network File System developed by Sun Microsystems. A file-sharing protocol that enables you to share file systems over the Internet and Intranet. NFS is used with both UNIX and non-UNIX computers.

NFS export: A directory that is published for access by NFS clients. The export specifies a directory to be exported and which machines have access to the directory. NFS exports are similar to CIFS shares in that they provide access to directories.

P

Pool: A group of storage locations.

Primary server: An active application server or monitoring agent.

Primary target: In a disaster recovery policy, this is the active target to which users are referred by the DFS root.

Q

qtree: A special directory of the root of a volume that behaves like a virtual subvolume with special attributes.

R

RAID: Redundant Array of Independent Disks enables file access even when a disk in a RAID group is damaged.

References: The DFS link targeting the selected physical item. For example, when you click a server under the Physical View tree, properties and associated DFS links appear.

Replica: A DFS root or DFS shared folder that provides an alternate path for a DFS link. NOTE: In Windows NT 4 terminology, this is referred to as an alternate volume.

Replica set: Two or more DFS roots or DFS shared folders that provide alternate paths for a DFS link.

Replication agent: The component deployed by the application server or monitoring agent component during configuration of storage policies that transfer CIFS data, or when you run a file differencing report. NOTES: Deployment of replication agents can be controlled through a machine's properties dialog box accessible from the Physical View. For data transfer using the NFS protocol, the replication agent must be installed manually.

Report schedule group: Enables you to set a schedule to automatically gather information. A report schedule group can be configured to start during off hours to offload network and computing resources during business hours. You can produce multiple reports from the data gathered without generating additional network traffic.

Report source group: Specifies the location where you want to gather information. It is assigned to a report schedule group. A report source group also enables you to specify batch files to run before and/or after the information is gathered.

Troubleshooting

Report type: Determines what information is gathered. Report types are assigned to report source groups.

S

Secondary target: SEE Standby target.

Server: The component that responds to requests from the client component, monitors the DFS namespace, and processes storage policies.

Shared folder: File or folder in the DFS namespace that can be accessed by users who have proper permissions. NOTE: In Windows NT 4, this is referred to as a DFS volume, leaf, or branch.

SID: Security identifier that uniquely identifies a Windows user or group.

Stand-alone DFS root: A DFS root that has its configuration information stored locally on the host server. The root has a single root target. When the root target is unavailable, the data referenced by links under the root is inaccessible.

Standby server: A machine that is standing by (not active) for the application server or a monitoring agent. During a failover, a standby server can become the active server.

Standby target: A target in a disaster recovery policy that is offline. During a failover, a standby target can become the active target.

Storage location: A combination of a server UNC path and the local path pointing to a directory in the file system. For example, \\rama:c:\ is a storage location representing the C drive on machine "rama" and \\secure.npb.com:/vol/vol0/myqtree is a storage location representing the qtree "myqtree" on volume vol0 on secure.npb.com.

T

Target: LINK TARGET: A shared folder, a DFS link, or a DFS root that is referenced by a DFS link. ROOT TARGET: A shared folder that is referenced by a DFS root. SEE ALSO Link target.

Trustee: The user account, group, or logon session to which an Access Control Entry (ACE) applies.

U

UID: User Identification Number. A unique number assigned to identify a user in UNIX environments.

UNIX file permissions: Control access to files and directories. Permissions can be applied to the owner of a file, a group, or everyone on the UNIX network.

W

Widelink namespace: A logical namespace hosted on a NetApp filer CIFS share that provides the benefits of a namespace without requiring additional Windows servers.

Index

Troubleshooting

D

Data migration	39
DFS link	
check status	41
DFS root	
check status	41

M

Machines	
status	41
Migration policy	
task status indicators	39
Monitor status	41
Monitoring status of link targets	39

N

NTFS Change Journal	35
---------------------------	----

O

OpenSSH	36
---------------	----

Q

qtree	
status	41
qtree	41

R

Replication	39
-------------------	----

S

SSH	36
Status indicators	39, 41
Status monitoring	39, 41
System status	41

T

Troubleshooting	
-----------------	--

browse namespace problems	30
DFS root problems	12
general problems	10
migration problems	17
name of machine is incorrect	34
NetApp filer problems	27
permission based namespace policy problems	34
problem accessing a UNIX machine when	
using SSH	36
problem configuring OpenSSH	36
problem installing a UNIX replication agent	34
problem taking snapshots of application	34
problems connecting to the application service	16
problems printing PDF files	33
problems running a policy	31
problems running batch files	31
problems selecting a monitoring agent	16
problems using NTFS change journal	35
replication problems	17
Report problems	14
snapshot access policy problems	33
Target problems	15
Windows 2000 incompatibility problems	15
Windows powered NAS ID problems	30
Windows storage server filer ID problems	30
Windows XP incompatibility problems	15
Troubleshooting	10

V

Volumes	
status	41
Volumes	41

